



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/607,206	06/27/2003	Sang Moo Song	8733.847.00-US	5817
30827	7590	04/05/2006		
MCKENNA LONG & ALDRIDGE LLP 1900 K STREET, NW WASHINGTON, DC 20006			EXAMINER NGUYEN, THANH NHAN P	
			ART UNIT 2871	PAPER NUMBER

DATE MAILED: 04/05/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

## Office Action Summary

Application No.

10/607,206

Applicant(s)

SONG, SANG MOO

Examiner

(Nancy) Thanh-Nhan P. Nguyen

Art Unit

2871

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 07 March 2006.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1,3-9,11-15,20,21,26 and 27 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1,3-9,11-15,20,21,26 and 27 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 27 June 2003 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some \* c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |  |   |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)   | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                                   | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152)             |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

### DETAILED ACTION

This communication is responsive to RCE dated 3/7/2006.

Claims 1, 3-9, 11-15, 20, 21, 26 & 27 are pending for the examination.

Claims 2, 10, 16-19, 22-25 are canceled.

#### **Claim Objections**

**Claim 1** is objected to because of the following informalities: Claim 1 currently read as, "... and a second line of liquid crystal ..." It should have read as, "... and a second horizontal line of liquid crystal ..."

**Claims 3-6** are objected to because of the following informalities: Claims 3-6 currently read as, "... according to claim 2..." It should have read as, "... according to claim 1..." since claim 2 has been canceled.

Appropriate correction is required.

#### **Claim Rejections - 35 USC § 103**

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

**Claims 1, 3, 5-9, 12-15, 20, 21, 26 & 27 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chung et al (U.S. 2002/0008792) in view of Kimura et al (U.S. 5,253,091).**

**Regarding claims 1, 3, 5-9, 15, 20, 21 & 26, Chung et al discloses a liquid crystal display panel, comprising: a plurality of gate lines (41n-1); a plurality of data lines**

(43n-1) crossing the plurality of gate lines; a plurality of liquid crystal cells defined by the gate and data lines, wherein each liquid crystal cell comprises a thin film transistor (45) at a crossing of the gate and data lines, and a pixel electrode (47) connected to the thin film transistor at a first side portion; a first parasitic capacitor formed between the plurality of data lines and pixel electrodes preceding adjacent ones of the plurality of data lines; a second parasitic capacitor formed between the plurality of data lines and pixel electrodes succeeding adjacent ones of the plurality of data lines; and a groove formed within a second side portion of the pixel electrode adjacent the plurality of data lines, wherein the second side portion is opposite the first side portion, [see figs. 4 & 6].

Chung et al lacks disclosure of the pixel electrode has a substantially diagonally symmetric shape.

However, regarding figs. 4 & 6, each of the pixel electrode (47) is patterned to be absent at the lower right and lower left corners, thereby being bilaterally symmetric about a vertical reference line crossing the center of the pixel area in the direction of the data lines to have the capacitance values  $C_{dp1}$  and  $C_{dp2}$  are substantially the same for the benefit of preventing the degradation of resolution in the device, [see par. 0040]. In order to have the pixel electrode having a substantially diagonally symmetric shape, according to figs. 4 & 6, a groove formed within a second side portion of the pixel electrode adjacent the plurality of data lines, wherein the second side portion is opposite the first side portion, would be placed at the upper part of the pixel within a second side portion, or as long as the groove is placed opposite with thin film transistor in diagonal direction. It has been determined that the rearrangement of parts is within the ordinary

level of skill, [see MPEP 2144.04 VI (C) Rearrangement of Parts]. Therefore, it would have been obvious to a person of ordinary skill in the art to place a groove within a second side portion of the pixel electrode, wherein the second side portion is opposite the first side portion, at the upper part of the pixel within a second side portion to make the pixel electrode has a substantially diagonally symmetric shape since the rearrangement of the parts is within the ordinary skill level, and for the benefit of reducing or nearly eliminating the resolution degradation of the liquid crystal display device.

Chung et al further lacks disclosure of a first horizontal line of liquid crystal cells having thin film transistors connected to preceding ones of adjacent data lines, and a second horizontal line of liquid crystal cells having thin film transistors connected to successive ones of adjacent data lines; wherein within the first horizontal line, consecutive ones of the liquid crystal cells are charged with pixel signals having alternating, opposite polarities; within the second horizontal line, consecutive ones of the liquid crystal cells are charged with pixel signals having alternating, opposite polarities; and wherein within the first and second horizontal lines, consecutive ones of the liquid crystal cells arranged within a vertical line, are charged with pixel signals having alternating, opposite polarities.

Kimura et al teaches the alternating of TFT connection to preceding ones of adjacent data lines, and the TFT connection to successive ones of adjacent data lines in every one horizontal line, and the use of dot inversion pixels for the benefit of reducing the screen flicker without increasing electric power consumption. This is true for

Art Unit: 2871

adjacent pixels in successive rows, as well as for adjacent pixels in successive columns, [see column 3, lines 5-55, and figure 4]. Therefore, at the time the invention was made, it would have been obvious to a person of ordinary skill in the art to arrange the TFT connection to preceding ones of adjacent data lines, and the TFT connection to successive ones of adjacent data lines in every one horizontal line alternatively besides the use of dot inversion pixels for the benefit of reducing the screen flicker without increasing electric power consumption.

**Regarding claim 12**, Chung et al lacks disclosure of the TFTs of consecutive ones of the liquid crystal cells arranged within a first horizontal line are coupled to preceding ones of the plurality of data lines.

Kimura et al discloses the TFTs of consecutive ones of the liquid crystal cells arranged within a first horizontal line are coupled to preceding ones of the plurality of data lines, [see fig. 4].

**Regarding claim 13**, Chung et al lacks disclosure of the TFTs of consecutive ones of the liquid crystal cells arranged within a second horizontal line are coupled to succeeding ones of the plurality of data lines.

Kimura et al discloses the TFTs of consecutive ones of the liquid crystal cells arranged within a second horizontal line are coupled to succeeding ones of the plurality of data lines, [see fig. 4].

**Also, regarding claim 14**, Chung et al lacks disclosure of the consecutive ones of the liquid crystal cells arranged within a horizontal line are charged with data signals having opposite polarity.

Kimura et al shows in figure 7, the successive gate electrodes of the TFT's 4a, 4b, 4c . . . which each drive a successive, respective pixel 5a, 5b, 5c . . . in the direction of the row are alternately connected to one of the two adjacent row signal conductors. All drain electrodes of the TFT's 4a, 4b, 4c . . . in a given row are connected to the column signal conductors of only one of the data drive circuits. However, the drain electrodes of TFT's in successive rows are alternately connected to the column signal conductors of the first data drive circuit 2 and the column signal conductors of the second data drive circuit 3. In this case, the method of driving includes the application of the drive waveform in the manner shown in figure 5 to each pixel, to drive successive pixels in the direction of the row with the same polarity, and to drive successive pixels in the direction of the column alternately with positive and negative polarities; that is when one pixel is driven by a positive data signal an adjacent pixel in the direction of a column is driven by a negative data signal, [see column 4, lines 1-41, and figure 7].

**All of the above listed features in claims 12-14** are described in Kimura's disclosure as being for the benefit of reducing the flicker in the direction of the column, and less electrical power consumption, [see col. 4, lines 23-24]. Therefore, at the time the invention was made, it would have been obvious to a person of ordinary skill in the art to use the way of Kimura et al for flipping and alternating of the pixel electrodes so that the area/ length/ parasitic capacitance of a side of a pair of pixel electrodes adjacent a portion of a single data line are substantially equal, and to modify the use of row inversion pixels (of Kimura et al, to have screen flicker reduced in the direction of

column, see column 4, lines 23-24) by using column inversion for the benefit of less electrical power consumption, and screen flicker reduced in the direction of row.

**Claim 27** is met the discussion regarding claim 26 rejection above.

**Claims 4 and 11 are rejected under 35 U.S.C. 103(a) over Chung et al in view of Kimura et al as discussed above, and further in view of Suzuki (U.S. 5,436,747).**

**Regarding claim 4**, Chung et al lacks disclosure of the first horizontal line and the second horizontal line are alternately arranged within the liquid crystal display panel, and wherein within a vertical line or liquid crystal cells, every two liquid crystal cells are liquid crystal cells from the first horizontal line.

Suzuki shows in figure 3 the alternating of TFT connection to preceding ones of adjacent data lines and the TFT connection to successive ones of adjacent data lines in every two horizontal lines for the benefit of reducing the screen flicker, and lowering the power consumption. Since the first and the second data drivers are not switched every two row conductors, as in figure 2, (instead of switching, the connection of each subpixel to each column conductor is changed), load on the data drivers decreases and the pixels can be driven by a circuit of relatively low power consumption. In other words, load on the data drivers is reduced and the pixels may be driven by a low power consumption circuit because it is the connection of the column conductors which is changed to invert the polarities of the first and the second data signals every two row conductors. This is done instead of using high speed, high amplitude electric switching, [see column 4, lines 63-68; column 5, lines 1-8; and figure 2, 3].



Therefore, at the time the invention was made, it would have been obvious to a person of ordinary skill in the art to arrange alternatively every two horizontal lines, and wherein within a vertical line of liquid crystal cells, every two liquid crystal cells are from the first horizontal line for the benefit of having reduced screen flicker and low power consumption.

**Regarding claim 11**, also missing from Chung et al, is the thin film transistors of every two consecutively arranged ones of the plurality of liquid crystal cells arranged within a vertical line are alternately coupled to adjacent ones of the plurality of data lines. This is the case of flipping and alternating of the pixel electrodes of every two horizontal lines so that the thin film transistors of every two consecutively arranged ones of the plurality of liquid crystal cells arranged within a vertical line are alternately coupled to adjacent ones of the plurality of data lines. Since Kimura et al teaches about flipping of the pixel electrodes of every one horizontal line, and Suzuki teaches about alternating of the pixel electrodes of every two horizontal lines, it would have been obvious to a person of ordinary skill in the art to modify to have flipping and alternating of the pixel electrodes of every two horizontal lines for the benefit of having reduced flicker and low power consumption.

### **Conclusion**

Any inquiry concerning this communication or earlier communications from the examiner should be directed to (Nancy) Thanh-Nhan P. Nguyen whose telephone number is 571-272-1673. The examiner can normally be reached on M-F/9-5:30.


Art Unit: 2871

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Robert Kim can be reached on 571-272-2293. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

(Nancy) Thanh-Nhan P Nguyen  
Examiner  
Art Unit 2871  
-- April 3, 2006 --

TN

  
ANDREW SCHECHTER  
PRIMARY EXAMINER